



Skladové prostory

1244 m², Česká Lípa, Nový Bor, Nemocniční

Cena na vyžádání



STANDARD TECHNICAL SPECIFICATION

SUPPORTING STRUCTURE

- Pad or pile foundations, insulated plinth, ground up to 30cm above floor
- Prefabricated concrete columns in 12 x 24m grid per span
- Prefabricated concrete or steel roof beams, clear height of 10m

FLOOR

- Floor: reinforced concrete floor, PE membrane, 100 mm thick, surface treated with hardener
- Load capacity of 50 kN/m², 60 kN point load
- Flatness according to DIN 1822, table 3, line 3

ROOF

- Corrugated steel sheets, mineral wool insulation, PVC membrane
- Free load capacity of 15 kg/m² for client's installations
- Min. 2% of eights in warehouse area
- Synthetic drainage system, emergency overflow

FACADE

- Horizontal sandwich panels with mineral wool insulation
- Prefabricated concrete facade around docks to approx. 4.5m height
- Double glazed windows in offices with insulated PVC profiles

DOCKS

- 1x electrically operated 3 x 3.2 m dock for each 1 500 sqm of hall
- Each dock equipped with hydraulic leveler, 40 kN capacity, PVC shelter, wheel guides
- 1x electrically operated 3 x 4.2 m drive-in gate for each 1 500 sqm of hall

HALL INSTALLATIONS

- Gas tubes, burners or infrared gas radiators, heating according to norms for warehousing
- 230V gridlines under roof, PE (galvanised) tank and pumps
- 200 kVA 10/0.4 kV transformer including influence of climate insulation
- 1x 400 kVA dry transformer station per each 125 000 sqm of hall

PRODUCTION UPGRADE (OPTIONAL)

- Increased facade and roof insulation
- Heating and ventilation in accordance with code for manufacturing (warehousing)
- 300 kVA 10/0.4 kV transformer including influence of climate insulation
- Increased percentage of daylight area

OFFICES

- 2-level custom designed in hall, incl. offices, social, locker rooms, day rooms, exit furniture and appliances
- Aluminium entrance door with canopy to entrance lobby
- Thin, opaque or PVC floor surfaces, suspended mineral ceiling panels
- Solid floor with covered terrace, wall tiles, and floor accessories
- PVC color trays below windows, 1x 220V socket per work place
- Server room with 2 split units and antistatic PVC floor
- Top cooling

OUTSIDE AREAS

- Hard areas from concrete panels, sloped for drainage
- 2m-high trash fence, entrance barriers and manual gate
- Green areas with grass, bushes, and trees



Skladové prostory

1 244 m², Česká Lípa, Nový Bor, Nemocniční

Cena na vyžádání

Celková plocha	1 244 m ²
Volná plocha k pronájmu	1 244 m ²
Minimální plocha	1 244 m ²
Čistá výška stropu	10 m
Nosnost podlah	5 t/m ²
Modul sloupů	—
Konstrukce	Železobetonová konstrukce
PENB	G
Referenční číslo	107284

1 244 m² skladových, výrobních a kancelářských prostor k pronájmu v Novém Boru. Prostory jsou vhodné pro logistiku, distribuci nebo lehkou výrobu. K dispozici do 12 měsíců po podpisu smlouvy.

Lokalita:

Park se bude nacházet na silnici I/9 spojující Prahu, Neratovice, Mělník, Českou Lípou, Nový Bor a Rumburk. Dále pokračuje přes hraniční přechod Rumburk/Ebersbach-Neugersdorf do Saská. Na území města se nachází jediná železniční stanice Nový Bor obsluhovaná dálkovou linkou R22 a regionální linkou L4.

Vybavení a služby:

- flexibilní jednotky (sklad / lehká výroba / kancelář / showroom)
- správa nemovitosti přímo v areálu
- údržba budov
- 9 parkovacích míst
- parkovací místa pro kamiony
- retenční rybník


Skladové/výrobní prostory:

- nosnost podlahy 5 t/m²
- světlá výška 10 m
- modul sloupů 12x24 m
- LED osvětlení 200 Lux
- ESFR spinkler system

Kanceláře:

- kancelářské prostory na míru
- klimatizace

Nájemce neplatí provizi.





Skladové prostory


1244 m², Česká Lípa, Nový Bor, Nemocniční

Cena na vyžádání

● For rent (existing building)

● For rent (new development)

● Rented





Skladové prostory

Cena na vyžádání

1244 m², Česká Lípa, Nový Bor, Nemocniční

TOTAL BUILT-UP AREA
BUILDING A1
BUILDING A2
BUILDING B
BUILDING C

47,308 sq m
24,586 sq m
14,323 sq m
7,155 sq m
1,244 sq m

WAREHOUSE
Column grid
Clear height
Floor loading
ESFR sprinkler system
LED lighting

12 m x 24 m
10 m
5 t/sq m

SUSTAINABILITY TRENDS
BREEAM New Construction level Excellent
Option for heat pumps and photovoltaics

